

JMG Cranes S.p.A.

Sales & Service Office

Via Bergamo, 142

26100 Cremona - Italy

t +39 0372 1786738

Production Plant

Via Sito Nuovo 14

29010 Sarmato (PC) - Italy

t +39 0523 8486


e info@jmgcranes.com



Data subject to change without prior notice
Edition 04/2020 © 2020 JMG Cranes S.p.A. All rights reserved
Rev. 1 - 04/2020



Electric Pick & Carry Cranes



MC 130S (metric)
Max Capacity 13,000 Kg

www.jmgcranes.com

JMG[®]
move to solution

MC 130S

RADIO-REMOTE CONTROL ON DRIVING, STEERING, BOOM MOVEMENTS, WINCH AND OTHER ACCESSORIES

FRONT-WHEELS DRIVE WITH COUNTER ROTATION


REMOVABLE COUNTERWEIGHTS

HYDRAULICALLY TELESCOPING PROPORTIONAL TYPE BOOM


FRONT STABILISING BAR

Options :

- HYDRAULIC WINCH
- HYDRAULIC JIB WITH HYDRAULIC EXTENSION
- BENDABLE MANUAL JIB WITH MANUAL EXTENSION
- NON-MARKING TIRES
- HYDRAULIC FORKS
- MAN BUCKET
-  ATEX CONVERSIONS
- CUSTOMIZED PAINTING



Load charts




Technical features


Max Capacity kg	13,000
Dimensions mm	4030x1850x1990

	Front-wheels drive. 2 electric motors AC 8,5 kW 80V Insulation class H	LMI.	Electronic safe load indicator and tilting moment limiter
	Total Kg. 14,500 Removable counterweights Kg. 4,000		Automatic braking system on all wheels
	80 V - 900 Ah 8 working hours		Fabricated from preformed and welded quality steel plate
	Front nr. 4 superelastic 300-15" Rear nr. 2 superelastic 250-15"		+65°/-5°
	Rear Steering angle -90°/+90°		Motor driven pump 23 kW - 96 V AC, Insulation class H

HOOK ON STABILISING BAR



HYDRAULIC WINCH



EU Standards CE

	UNI ISO 4301-2: A1
	2006/42 CE-2014/30 UE- 2014/35 UE- 2000/14 e and subsequent modifications
	EN 13000:2014 ANSI/ASME B30.5-2011 and subsequent modifications



Dimensions

